

**NATROCHEM, INC.**Post Office Box 1205
Savannah, Georgia 31402-1205
(912) 236-4464**MATERIAL SAFETY
DATA SHEET****BUTYL TUADS DLC®-A**

Date Revised: September 12, 1997

Page 1 of 4

SECTION I - PRODUCT IDENTIFICATIONTRADE NAME: Butyl Tuads DLC-A
CHEMICAL NAME: Tetrabutylthiuram disulfide on silicon dioxide

HMIS RATING	
Health	1
Flammability	1
Reactivity	0

SECTION II - HAZARDOUS INGREDIENTS

The component(s) listed below is identified as a hazardous chemical under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

INGREDIENT	CAS #	ACGIH (TLV)	OSHA (PEL)	UNITS
Silicon Dioxide	7631-86-9	10	6	mg/m ³

SECTION III - PHYSICAL DATABoiling Point: N/DA
Vapor Pressure (mm Hg): N/DA
Vapor Density (Air = 1): N/DA
Solubility in Water: Negligible
Appearance and Odor: Brown, free flowing powder with sweetish odor.
Specific Gravity: 1.22 (calculated)
Percent Volatiles: N/DA
Evaporation Rate: N/DA**SECTION IV - FIRE & EXPLOSION DATA**FLASH POINT (Method Used): 280°F (COC)
FLAMMABLE LIMITS: N/DA
AUTOIGNITION TEMPERATURE: N/DA

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, and foam.

SPECIAL FIRE FIGHTING PROCEDURES: Positive pressure self-contained breathing apparatus.

UNUSUAL FIRE & EXPLOSION HAZARDS: None known.

SECTION V - HEALTH HAZARD DATA

CHRONIC HEALTH EFFECTS: An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed for an average of 18 years. No adverse effects were noted in complete medical examination (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposure. Laboratory studies have also been conducted in small animals via inhalation to levels of precipitated silica dust of up to 126 mg/m³ for periods from six months to two years. Although precipitated silica was temporarily deposited in the animals lungs, most of the deposited material was cleared soon after the dust exposure ended. The results of all studies performed by, or known to, PPG indicate a very low order of pulmonary activity for synthetic precipitated silica.

**MARKETED BY
HARWICK STANDARD
DISTRIBUTION CORPORATION**

60 S. Seiberling Street • Akron, Ohio 44305

SECTION V - HEALTH HAZARD DATA (cont)

PRIMARY ROUTE OF ENTRY- Inhalation & skin.

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN: None.

NTP: No

IARC: No

OSHA: No

EFFECTS OF EXPOSURE-

EYES- Mildly irritating. Excessive contact with powder can cause drying of mucous membranes of eyes due to absorption of moisture and oils.

SKIN- Mildly irritating. Will discolor skin by reaction with iron and copper metals in the skin.

INHALATION- Nuisance dust. Excessive contact with powder can cause drying of mucous membranes of nose and throat due to absorption of moisture and oils. This material can also cause nasal irritation and nosebleeds.

INGESTION- Not significantly toxic. Do not ingest alcoholic beverages immediately before and after handling this material (antabuse reaction).

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE- Persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection.

SECTION VI - EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: Immediately rinse with clean water for 15 minutes. Retract eyelids often. If irritation persists, seek medical attention.

SKIN CONTACT: Immediately remove contaminated clothing. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. Seek medical attention if ill effect or irritation develops.

INHALATION: If overcome by exposure, remove victim to fresh air. Keep warm and quiet. Give artificial respiration.

INGESTION: Call physician if subject has used alcohol within 48 hours.

SECTION VII - REACTIVITY DATA

STABILITY: Stable.

MATERIALS TO AVOID- Avoid alteration of product properties before reuse. Calcining, which may result in crystalline formation or mixing with additives may alter toxicological properties. Strong acids and reducing agents.

CONDITIONS TO AVOID- Avoid high temperatures (>800 C) treatment.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, nitrogen, and sulfur when burned.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: MINIMIZE SPILL AREA. Vacuum spill material and place in closed plastic bags for disposal.

WASTE DISPOSAL METHOD: Not a RCRA hazardous waste. Dispose of according to applicable environmental regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use a respirator such as 3M 9900 or equivalent for protection against pneumoconiosis producing dusts.

VENTILATION: Provide explosion proof ventilation as required to control airborne dust levels. The sum total of all ingredients may emit vapors during normal processing. All possible health effects are not known and individual sensitivities will vary. Effective exhaust ventilation should always be provided to draw dust, fumes and vapors away from workers to prevent routine inhalation. Ventilation should be adequate to maintain ambient workplace atmosphere below the limits listed in Section V.

PROTECTIVE GLOVES: Impervious gloves to protect against contact with product.

EYE PROTECTION: Safety goggles.

OTHER PROTECTIVE EQUIPMENT: Protective clothing, eye wash station, safety shower.

SECTION X - SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Handling can create explosive dust clouds. Eliminate ignition sources, use explosive proof equipment. Conveying and processing equipment should be spark-proof, well bonded and grounded. Avoid dust accumulations.

OTHER PRECAUTIONS: Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Launder contaminated clothing before reuse.

SECTION XI - REGULATORY INFORMATION

TOXIC SUBSTANCE CONTROL ACT (TSCA):

The components of this product are contained on the Inventory of the Toxic Substance Control Act.

SARA TITLE III INFORMATION:

SECTION 313 - TOXIC CHEMICALS:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):

CAS REGISTRY #	CHEMICAL NAME	PERCENT BY WEIGHT
----------------	---------------	-------------------

This product does not contain a toxic chemical in excess of 1% of the mixture.

This information must be included in all MSDS's that are copied and distributed for this material.

SECTION XI - REGULATORY INFORMATION (Cont.)

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES:

This product does not contain an extremely hazardous substance.

SECTION 311/312 - HAZARD CATEGORIES:

The physical and health hazard categories for this product are:

Fire Hazard: None

Sudden Release of Pressure Hazard: None

Reactivity Hazard: None

Immediate (Acute) Health Hazard: Silicon Dioxide

Delayed (Chronic) Health Hazard: None

TRANSPORTATION INFORMATION:

DOT Shipping Name: Not DOT regulated

DOT Identification Number:

SECTION XII - OTHER INFORMATION

Revision Note: Revised due to change in Section VII. Changed material from a RCRA waste to not a RCRA waste.

Prepared by: James L. Pye, Jr.

Title: Safety Coordinator

N/A = Not applicable N/D = Not determined N/DA = No Data Available

N/E = Not established

The information given in this MSDS was obtained from sources which we believe are reliable. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, Natrochem, Inc. makes no warranty express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.